



Hydraulic hand-operated tool HP 60 C with C-compression head, rotating 180°

double piston pump for rapid motion of the die-set

automatic safety relief valve to avoid overpressure

force of pressure: 60 kN

changeable dies type A



Hydraulic hand-operated tool HP 60 R with round-compression head, rotating 180°

double piston pump

automatic safety relief valve to avoid overpressure

force of pressure: 60 kN

changeable dies type B



Hydraulic hand-operated tool HP 60 H with H-compression head, rotating 180°

double piston pump for rapid motion of the die set

automatic safety relief valve to avoid overpressure

force of pressure: 60 kN

changeable dies type C

Material	Pressform	Pressbereich mm ²
material	compression form	compression range mm ²
Cu	Dornkerbung	10 - 95
	deep indent pressing	
Cu	Doppeldornkerbung	10 - 95
	double deep indent pressing	
WMS	WMS-Pressung	10 - 95
	WMS-Pressung	

	Länge mm	Gewicht kg	Art.-No.
	length mm	weight kg	
C-Presskopf	520	3,2	57003-00
C-compression head			
R-Presskopf	480	3,5	57000-00
R-compression head			
Transportkoffer	605	4,8	58005-00
Transport case			
H-Presskopf	370	2,3	57005-00
H-compression head			
Transportkoffer	605	4,8	58005-00
Transport case			